Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Pin Assignments

Following are the pin assignments for your ISA I/O Card.

Jameco Part Number 171651

Parallel Port 24-Pin Female Connector (P1)					
Pin	**Signal**	**Pin**	**Signal**	**Pin**	**Signal**
1	Strobe	10	Acknowledge	19	Ground
2	Data 0	11	Busy	20	Ground
3	Data 1	12	Paper Empty	21	Ground
4	Data 2	13	Select	22	Ground
5	Data 3	14	Auto Feed	23	Ground
6	Data 4	15	Error	24	Ground
7	Data 5	16	Init	25	Ground
8	Data 6	17	Select Input	26	Ground
9	Data 7	18	Ground		

Hardware Specifications

Your ISA parallel port has the following hardware specifications:

- One Ultra High Speed Bi-directional Parallel Port
- Advanced Chipset
- Max. Speed: Up to 21.4 MB/s
- 16-bit ISA Interface
- Compatible with all IBM PC/AT and AT Compatible Computers
- Supports LPT s 1-7 and IRQs 3-15
- 32 Byte FIFO Buffer
- Supports ECP Mode DMA Channels 1, 2 & 3

Technical Specifications

- Computer Compatibility: 486/586/Pentium/Pentium II/III
- Operating System Compatibility: Win 95, 98, NT, 2000, Linux
- ECP/EPP Interface
- Parallel Connector: 1 x 25-Pin D-Sub Female